

miniwelder tex2: The expert for thin membranes

The miniwelder tex2 is ideal for thin materials. Thanks to the welder's optimized wedge geometry, the miniwelder tex2 welds 0.1 to 1.0 mm membranes perfectly. With the help of its revolutionary control system, welding start-up is child's play. The welder is simple and intuitive to use. You will be convinced by the performance of the miniwelder tex2.

Hot-wedge welding machine

miniwelder tex2

- Lightweight (3.5 kg)
- Welding speed of up to 7.5 m per minute
- Revolutionary chainless drive technology
- Ideal for thin membranes
- Good performance at an affordable price



Technical data

Voltage	V~	120 / 230
Frequency	Hz	50 / 60
Max. power	W	800
Temperature	°C	60–480
Hot wedge material		Stainless steel/copper
Weld seam width	mm	20
Max. overlap	mm	100
Speed	m/min	0.4 - 7.5
Dimensions (L × W × H)	mm	228 × 228 × 170
Weight	kg	3.5
Conformity marking		CE
Weldable materials		PE, PVC, TPO, PP 0.1 - 1.0 mm

Delivery contents

Instruction manual, transport box, hex wrench, cleaning brush

Article no.

miniwelder tex2, 230V/800W (stainless steel for PVC), EU plug	154.883
miniwelder tex2, 230V/800W CU (copper), EU-plug	154.885



Accessories



156.668 (230 V)
159.518 (120 V)
 Hot wedge, 20 mm
 Chromium steel (for PVC)



156.616 (230 V)
159.517 (120 V)
 Hot wedge, 20 mm copper



156.818
 Silicone drive roller,
 22 x 50 mm, without test
 channel (1 pair)



158.720
 Miniwelder guide bar

