

VARIMAT 700



To the product



Technical data

Voltage	230 V; 400 V	
Frequency	50/60 Hz	
Power	3680-5700 W	
Speed	1.0-12.0 m/min	3.28-39.37 ft/min
Temperature	100-620 °C	212.0-1148.0 °F
Air volume adjustable	Yes	
Welding nozzle / seam width	40 mm	1.57 in
Welding materials	ECB; EPDM; EVA; FPO; PIB; PO; PVC; PVC-P; TPE; TPO; TPU	
LQS	Yes	
Brushless blower motor	Yes	
Brushless drive motor	Yes	
Length	605.0 mm	23.81 in
Width	335.0 mm	13.18 in
Height	373.0 mm	14.68 in
Weight	37.5 kg	82.67 lb
Power cable length	5.0 m	16.4 ft
Approvals	CB Certification; CE; UKCA	
Protection class	I	
Country of origin	CH	



VARIMAT 700

Scope of delivery

Welding plate; Wire brush, stainless steel; Nozzle adjustment gauge VARIMAT 700/500/300; Screwdriver, Torx T20; Allen wrench 4 mm; Rolling Transport Case VARIMAT 700/500/300

Product items

- 173.180 VARIMAT 700, 230V/3680W, 40mm, w/o cable
- 173.181 VARIMAT 700, 400V/5700W, 40mm, CEE 5/16
- 174.614 VARIMAT 700, 230V/3680W, 40mm, °F, w/o plug